

# Product sheet



LEGRAND

Fault signalling contact DX<sup>3</sup> - 6 A 250 V~ - 0.5 module

REF. 406252 | EAN. 3245064062527

[> Visit e-catalogue](#)

## Product characteristics

- Signalling, remote tripping auxiliaries and motorised controls DX<sup>3</sup>
- Signalling auxiliaries fork busbar adapted - To fit on the Left - hand side of DX<sup>3</sup> and TX<sup>3</sup> devices - Maximum number of auxiliaries per device : - 3 signalling auxiliaries or - 2 signalling auxiliaries + 1 remote tripping auxiliary - Allow insertion of the supply busbar, top side - No tool required for joining together the auxiliary and the main device. - No tool required for joining together the auxiliary and the main device. Auxiliary contact - 6 A - 250 V~ (changeover switch) - For MCBs, RCBOs, RCCBs, isolating switch or remote trip isolating switch - Indicates the position of the contacts of its associated device - Fault signalling contact - 6 A - 250 V~ (changeover switch) - For MCBs, RCBOs, RCCBs, - Indicates the fault tripping of its associated device - Number of modules : 0,5

## Documentation

### TECHNICAL DOCUMENTATION

→ [LE11861AC.pdf](#) | PDF (3.87Mo)

[F01548EN-00.pdf](#) | PDF (0.58Mo)

### CAD & Design specs / BIM

[406252.dwg](#) | DWG (0.2Mo)

### CATALOGUE PAGE & OTHERS

[ex223001\\_0073.pdf](#) | PDF (0.08Mo)

### Agreements & Certificates

[LGRP-01227-V01.01-EN.pdf](#) | PDF (0.64Mo)