

Product sheet



SYNERGY™ LEGRAND

Synergy™ Sleek - universal rotary dimmer (LED & Halogen) - 300W - Polished Stainless Steel

REF. 832351 | EAN. 3414970662644

> [Visit e-catalogue](#)

Product characteristics

- 100V~ to 250V~, 50/60Hz 5W to 75W for dimmable LED and fluocompact, 5W to 300W for halogen and incandescent
- Can be associated with one or several push - buttons, for ON/OFF or dimming control.
- Integrates memory level function : when switched ON, gradually (2 s) lights up at the level set before last switch OFF.
- Screwless cover plate is square 86x86 mm, product thickness is 4mm (once is installed onto the wall).
- Equipped with overvoltage and short-circuit protection

Recommendation / Restriction

- Recommended inside use only

The product's benefits

Installation

- Without neutral can be retro-fitted into existing point of lighting

Usage

- Rotary shaped knob for easy grip allowing the dimming of enabled charges (included LED charges)

Avantages

- Plate and knob are made in the same ferritic Stainless Steel - Grade 430, with a chromium plating which bring a better rusting resistance and a nicer finish
- Rotary dimmer for all type of lamps including dimmable LED and fluocompact
- Delivered with screws for flush & surface boxes in both plastic and metal boxes

Documentation

TECHNICAL DOCUMENTATION

→ [LE08934AA_EN-AR.pdf](#) | PDF (3.11Mo)

[F02305EN-00.pdf](#) | PDF (0.62Mo)

Agreements & Certificates

[OC / CB-SE-115438](#) | (0.62Mo)

CATALOGUE PAGE & OTHERS

[ex223001_0727.pdf](#) | PDF (0.08Mo)