

Product sheet



LEGRAND

Flush mounting metal socket Green'up Access - locked - IP55-IK10 - German standard

REF. 077857 | EAN. 3414970321299

> [Visit e-catalogue](#)

Product characteristics

- Green'up Access sockets 16 A - 230 V - 16 A EV - for electric vehicles - Used for safely charging rechargeable electric and hybrid vehicles which take Mode 2 cord (compatible with Mode 1) - Connected to the consumer panel via one $3 \times 2.5 \text{ mm}^2$ dedicated line (1 line per socket) protected by 30 mA - 20 A C curve, type A or Hpi RCBO (or 30 mA type A or HPI RCCB + 20 A C curve circuit breaker) - Recomm ended installation height : 1.30 m from the floor - Suitable for residential and workplace use
- Mode 1 and Mode 2 sockets - 16 A EV - Heavy - duty mechanisms with silvered contacts - single-phase sockets - screw connection - 230 V - Supplied with base Cat.No 0 904 78 for hanging up the vehicle charging cable control box - For charging 1 vehicle - Conform to IEC 60 - 884 - 11P 55 - IK 10 flush-mounting - metal socket with locked flap cover - 250 different combinations - Suitable for installation In =rivate houses, lock - up garages, parking lots, etc - Supplied complete with plate and support - Mounting In =-gang Batibox flush-mounting box depth 50 mm - Can be surface mounted with box Cat.No 0 778 90 - Dimensions (H x W x D) : 110 x 110 x 13.5 mm - Supplied complete with a unique set of 2 keys In =rder to restrict access to the socket - German standard socket outlet

Documentation

TECHNICAL DOCUMENTATION

F03321EN-03.pdf | PDF (0.88Mo)

F03321FR-03.pdf | PDF (0.85Mo)

LE06549AD.pdf | PDF (1.08Mo)

Agreements & Certificates

OC / CB-FR_720173 | (0.39Mo)

CATALOGUE PAGE & OTHERS

ex223001_0514.pdf | PDF (0.19Mo)

ex223001_0513.pdf | PDF (0.11Mo)