

# Product sheet



PLEXO™ LEGRAND

Plexo™ - german standard socket outlet with auto terminals 16A 250V - Mechanism - White

REF. 069640L | EAN. 3414971880658

The white Plexo composable waterproof socket-outlet can be used to connect electrical or electronic equipment in any location where resistance to water, dust and impact is required. For indoor or outdoor use.

> [Visit e-catalogue](#)

## Description

The white Plexo composable waterproof socket-outlet can be used to connect electrical or electronic equipment in any location where resistance to water, dust and impact is required. For indoor or outdoor use.

### Product characteristics

- Product to be completed either with a surface-mounted box or a flush-mounted support frame.
- IP55: protected against dust and water spray from all directions
- IK08: 5 joules shock resistance.
- 2P+E 16A 250V socket outlet. Automatic terminals : quick connection without tools with colour coding.

## The product's benefits

### Installation

- A 90° symmetrical socket mechanism for horizontal or vertical mounting on surface-mounted boxes or flush-mounted support frames. The mechanism is easy to install without tools and can be removed by simply pressing on the sides. The clipping system ensures high resistance to wire pressure.

### Usage


- Completely white product adapted to environments where hygiene is important (germ-bearing dirt is immediately visible)

### Avantages

- A 90° symmetrical mechanism for horizontal or vertical mounting on surface-mounted boxes or flush-mounted support frames.
- A 4-point (1/4 turn) front closure to ensure waterproofness whatever the configuration of the installation.

## Documentation

### TECHNICAL DOCUMENTATION


-  F03972FR-00.pdf | PDF (0.96Mo)
-  F04054EN-00.pdf | PDF (0.96Mo)
-  F03972EN-00.pdf | PDF (0.96Mo)






### CAD & Design specs / BIM

### CATALOGUE PAGE & OTHERS

-  ex223001\_0794.pdf | PDF (0.11Mo)

### Agreements & Certificates

 3D\_LG-069640L.stp | IFC (1.36Mo)  
BIM-LEGRAND-PLEXO-2023-FRANCAIS.rvt | RVT (158.35Mo)  
BIM-LEGRAND-PLEXO-2023-ENGLISH.rvt | RVT (161.4Mo)

 OC / CB-FR\_718712/A1 | (0.55Mo)  
 AENOR-030/002645 | (0.59Mo)  
 SNI-824 220292 | (0.49Mo)  
 KSC-JW04001-24001 | (3.79Mo)  
 VDE-40059394 | (0.44Mo)