

Product sheet



DSX TSE 320 LEGRAND

DSX Transfer switching equipment TSE Frame 2(320A)
- 3 poles - Rated current = 250A - fixing on plate

REF. 424121 | EAN. 3414971921283

> [Visit e-catalogue](#)

Product characteristics

- Rated insulation voltage $U_i = 1000V$, rated impulse withstand voltage $U_{imp} = 12kV$, dielectric strength 50 Hz 1 min = 10kV
- Climatic condition according to IEC/EN 60947 - 1 Annex Q, Cat. F subject to temperature, humidity, vibration, shock and salt mist.
- Answer for standard market needs, compact design, innovation with pop up indicators, total coordination with legrand mccb and mcb ranges
- Complete range of accessories: auxiliary contacts (NO+NC), rotary handles, locking accessory, sealable terminal shields IP40, phase barriers, spreaders

The product's benefits

Usage

- Small power distribution, back-up power, ensure continuity of electrical system

Avantages

- Full integrated with XL³S
- Common features with DPX³, double visible check of contacts

Documentation

TECHNICAL DOCUMENTATION

→ [LE14018AA.pdf](#) | PDF (3.89Mo)

CATALOGUE PAGE & OTHERS

[ex223001_0241.pdf](#) | PDF (0.12Mo)

[ex223001_0238.pdf](#) | PDF (0.14Mo)