

# Product sheet



## X-LIGHT 360 LEGRAND

X-Light 360 Recessed emergency lighting non permanent 100 lumens 1h standard

REF. 660032 | EAN. 3414972238779

> [Visit e-catalogue](#)

## Product characteristics

- Standard Version
- Lumen output : 100
- Duration : 1H
- Operating mode: Non-maintained (NM)

## The product's benefits

### Installation

- Removable terminal (plug-in) allowing quick installation

### Avantages

- Thanks to QR code engraved on emergency lighting unit, you have an instant access to data sheet, technical information... etc
- X-light 360 offers a discreet solution for perfect integration into all types of buildings with Thickness 2 mm
- Our packaging are 100% recyclable 0 Plastic and made at 80% from recycled carton

## Documentation

### TECHNICAL DOCUMENTATION

- [LE13296AD.pdf](#) | PDF (0.56Mo)
- [S000118532FR\\_3.pdf](#) | PDF (3.96Mo)
- [S000118532EN\\_3.pdf](#) | PDF (3.96Mo)

### CAD & Design specs / BIM

- [URA SPOT Standard - Non Permanent-ENG.rfa](#) | RFA (0.93Mo)
- [URA SPOT Standard - Non Permanent.rfa](#) | RFA (0.93Mo)

### CATALOGUE PAGE & OTHERS

- [ex223001\\_0905.pdf](#) | PDF (0.06Mo)
- [LG-660032.zip](#) | ZIP (0.02Mo)

### Agreements & Certificates

- [AENOR-007/001913](#) | (0.9Mo)
- [OC / CB-ES2591-M1-AENOR](#) | (0.41Mo)
- [AENOR-007/001950](#) | (0.83Mo)
- [ENEC-ENEC/001218](#) | (0.5Mo)
- [LGRP-01887-V01.01-EN.pdf](#) | PDF (0.85Mo)



ENEC-ENEC/001255 | (0.46Mo)